

Model	Wymiary montażowe [mm]			Wymiary wózka [mm]													
	H	H ₁	N	W	B	B ₁	C	L ₁	L	G	M	T	T ₁	T ₂	H ₂	H ₃	
HGW15CC	24	4	16	47	38	4,5	30	39,4	61,4	5,3	M5	6	8,9	6,95	4,5	5,5	
HGW20CC								50,5	77,5								
HGW20HC	30	5	22	63	53	5	40	65,2	90,3	12	M6	8	10	9,5	6	7	
HGW25CC								58	83								
HGW25HC	36	6	24	70	57	6,5	45	78,6	103,6	12	M8	8	14	10	6	9	
HGW30CC								70	97,4								
HGW30HC	42	6	31	90	72	9	52	93	120,4	12	M10	8,5	16	10	6,5	10,8	
HGW35CC								80	112,4								
HGW35HC	48	8	33	100	82	9	62	105,8	138,2	12	M10	10,1	18	13	9	12,6	
HGW45CC								97	138								
HGW45HC	60	10	38	120	100	10	80	128,8	169,8	12,9	M12	15,1	22	15	8,5	20,5	
HGW55CC								117,7	165,7								
HGW55HC	70	13	44	140	116	12	95	155,8	203,8	12,9	M14	17,1	26,5	17	12	19	
HGW65CC								144,2	198,2								
HGW65HC	90	15	54	170	142	14	110	203,6	257,6	12,9	M16	25	37,5	23	15	15	

Nośność, moment statyczny wózków liniowych HIWIN

Model	Nośności		Momenty statyczne			Waga	
	C _{dyn} [N]	C ₀ [N]	M ₀ [Nm]	M _x [Nm]	M _y [Nm]	Wózek	Szyna
						[kg]	[kg/m]
HGW15CC	11380	25310	170	150	150	0,17	1,45
HGW20CC	17750	37840	380	270	270	0,51	
HGW20HC	21180	48840	480	470	470	0,52	2,21
HGW25CC	26480	56190	640	510	510	0,70	
HGW25HC	32750	76000	870	880	880	0,80	3,21
HGW30CC	38740	83060	1060	850	850	1,42	
HGW30HC	47270	110130	1400	1470	1470	1,44	4,47
HGW35CC	49520	102870	1730	1200	1200	2,03	
HGW35HC	60210	136310	2290	2080	2080	2,06	6,3
HGW45CC	77570	155930	3010	2350	2350	2,54	
HGW45HC	94540	207120	4000	4070	4070	3,69	10,41
HGW55CC	114440	227810	5660	4060	4060	5,38	
HGW55HC	139350	301260	7490	7010	7010	5,96	15,08
HGW65CC	163630	324710	10020	6440	6440	9,17	
HGW65HC	208360	457150	14150	11120	11120	12,89	21,18